Precision Engineering

Maximum Performance



CE

CTS-4022

BOX MOTION SIDE SEALER MACHINE







CTS-4022

BOX MOTION SIDE SEALER MACHINE

CTS Series – Kota Pack machines are equipped with advanced technology solutions that combine high speed with superior packaging quality. Engineered with high-grade components and modern design principles, the system delivers long-lasting and reliable performance.
Featuring a center-folded single-roll film structure, independent side sealing, and a servo-controlled cross sealing system, the CTS Series ensures maximum efficiency and precision. Its quiet, vibration-free, and robust chassis construction enables uninterrupted operation while maintaining high performance and continuity across production processes. With a user-friendly interface, the CTS Series offers effortless operation, helping achieve maximum productivity with minimal operator intervention.

Highlights *Features*

- Automatic product length detection and adjustment with sensor and encoder-controlled system
- High production performance with servo-controlled sealing bar and continuous motion system
- Compatible with PE and Polyolefin films, operable within the 7–100 micron range
- Quick adaptation to different packaging dimensions and consistent packaging quality
- 100-recipe memory, multi-language 10" touch screen, and USB update support
- Efficient production with low energy consumption and minimum film waste
- Fast film changeover and tension-controlled scrap film rewinding system
- Fully automatic production structure requiring no operator intervention
- Precise and reliable sealing with ceramic-coated sealing blades
- Advanced protection systems for product, operator, and machine safety
- Design and production in compliance with CE standards

YOUTUBE LİNK

Options

- Printed film registration/control system
- Closing conveyor system
- Control via tablet or smartphone
- Remote access module

Installed Capacity	6000 Watt	**Average Consumption**	4800 Watt
Max. Product Width	370 mm	**Max. Proudct Height**	200 mm
Conv. Belt Width	410 mm	**Mühürleme Barı Uzunluğu**	520 mm
Machine Dimession	3000 x 1650 x 1450 mm	**Makine Ağırlığı**	1000 Kg
Useable Films	PE - POF (7-80 µ)	**Hava Basıncı**	6 Bar

Units *You Can Use Together*







KOTA PACK Smart Solutions in Packaging

Precision Engineering

Maximum Performance



CTS-4022

GEZER ÇENE YAN YAPIŞTIRMA SHRINK MAKİNESİ







CTS-4022

GEZER ÇENE YAN YAPIŞTIRMA SHRINK MAKİNESİ

CTS Serisi - Kota Pack makineleri, yüksek hız ve üstün ambalaj kalitesini bir araya getiren ileri teknoloji çözümleriyle donatılmıştır. Kaliteli komponentler ve modern mühendislik anlayışıyla tasarlanan sistem, uzun ömürlü ve güvenilir performans sunar. Çift katlı tek bobin yapısı ile bağımsız yan yapıştırma ve servo kontrollü ön yapıştırma sistemine sahip olan CTS Serisi, maksimum verimlilik ve hassasiyet sağlar. Sessiz, titreşimsiz ve sağlam gövde yapısı sayesinde kesintisiz çalışma imkânı sunarken, üretim süreçlerinde yüksek performans ve süreklilik sağlar. Kullanıcı dostu arayüzü ile kolay kullanım sunan CTS Serisi, minimum operatör müdahalesiyle maksimum üretkenlik elde edilmesine yardımcı olur.

Öne Çıkan *Özellikler*

- Sensör ve encoder kontrollü sistem ile otomatik ürün boyu algılama ve ayarlama
- Servo kontrollü kesme çenesi ve sürekli çalışma sistemi ile yüksek üretim performansı
- PE ve Poliolefin filmlerle uyumlu, 7-100 mikron aralığında çalışma imkânı
- Farklı ambalaj ölçülerine hızlı adaptasyon ve sürekli ambalaj kalitesi
- 100 ürün hafızası, çok dilli 10" dokunmatik ekran ve USB güncelleme desteği
- Düşük enerji tüketimi ve minimum film sarfiyatı ile verimli üretim
- Hızlı film değişimi ve gergi kontrollü fire sarma sistemi
- Operatör müdahalesi gerektirmeyen tam otomatik üretim yapısı
- Seramik kaplamalı yapıştırma bıçakları ile hassas ve güvenilir yapıştırma
- Ürün, operatör ve makine güvenliği için gelişmiş koruma sistemleri
- CE standartlarına uygun tasarım ve üretim

Opsiyonlar

- Baskılı film kontrol sistemi
- Kapamalı konveyör sistemi
- Tablet veya telefon üzerinden kontrol
- Uzaktan erişim modülü

YOUTUBE LİNK

Max. Kapasite*	120 ad/dk	**Max. Konveyör Hızı**	37 m/ min
Mühürleme Barı Uzunluğu	520 mm	**Besleme Voltajı**	380V, 50 Hz
Max. Ürün Ölçüleri	3000 x 1650 mm	**Makine Ağırlığı**	750 Kg
Konveyör Bant Genişliği	550 mm	**Film Tipi**	PE - POF (7-100 µ)

**Maksimum kapasite, ürün ebatlarına ve ürün çeşidine göre değişkenlik göstermektedir. En iyi cevap için iletişime geçiniz.*

Birlikte Kullanabileceğiniz *Üniteler*







KOTA PACK Smart Solutions in Packaging