Precision Engineering

Maximum Performance



CE

S-7022 | CONTINUOUS SIDE SEALER MACHINE







S-7022

CONTINUOUS SIDE SEALER MACHINE

The S-Series machines are equipped with high-tech solutions that combine high speed and superior packaging quality. Designed with quality components and a modern engineering approach, the system offers long-lasting and reliable performance.
Featuring a dual-layer single-coil structure with an independent side-sealing and a servo-controlled pre-sealing system, the S-Series provides maximum efficiency and precision.
While offering the possibility of uninterrupted operation thanks to its quiet, vibration-free, and robust body structure, it ensures high performance and continuity in production processes. Offering ease of use with its user-friendly interface, the S-Series helps to achieve maximum productivity with minimum operator intervention.

Highlights *Features*

-
- Automatic product length detection and adjustment via sensor and encoder-controlled system
- High production performance with servo-controlled cutting jaws and continuous operation system
- Compatibility with PE and Polyolefin films, capable of operating in the 7–100 micron range
- Rapid adaptation to different packaging sizes and consistent packaging quality
- 100-product memory, multilingual 10" touchscreen, and USB update support
- Efficient production with low energy consumption and minimal film waste
- Fast film change and tension-controlled scrap rewinding system
- Fully automatic production structure requiring no operator intervention
- Precise and reliable sealing with ceramic-coated sealing blades
- Advanced protection systems for product, operator, and machine safety
- Design and production in compliance with CE standards

YOUTUBE LİNK

Options

- Printed film control system
- In-feed conveyor system
- Control via tablet or smartphone
- Remote access module

Max. Capacity*	65-70 ad/dk	**Max. Conv. Speed**	37 m/ min
Sealing Bar Lenght	700 mm	**Power Supply**	380V, 50 Hz
Max. Product Dimmesion	670x200 mm	**Machine Weight**	950 Kg
Conv. Belt Width	700 mm	**Film Type**	PE - POF (7-100 µ)

**Maximum capacity varies depending on product dimensions and type. Please contact us for the best solution.*

Birlikte Kullanabileceğiniz *Üniteler*







Precision Engineering

Maximum Performance



CE

S-7022

SÜREKLİ KESİM YAN YAPIŞTIRMA SHRINK MAKİNESİ







S-7022

SÜREKLİ KESİM YAN YAPIŞTIRMA SHRINK MAKİNESİ

S Serisi makineler, yüksek hız ve üstün ambalaj kalitesini bir araya getiren ileri teknoloji çözümleriyle donatılmıştır. Kaliteli komponentler ve modern mühendislik anlayışıyla tasarlanan sistem, uzun ömürlü ve güvenilir performans sunar.
Çift katlı tek bobin yapısı ile bağımsız yan yapıştırma ve servo kontrollü ön yapıştırma sistemine sahip olan S Serisi, maksimum verimlilik ve hassasiyet sağlar.
Sessiz, titreşimsiz ve sağlam gövde yapısı sayesinde kesintisiz çalışma imkânı sunarken, üretim süreçlerinde yüksek performans ve süreklilik sağlar. Kullanıcı dostu arayüzü ile kolay kullanım sunan S Serisi, minimum operatör müdahalesiyle maksimum üretkenlik elde edilmesine yardımcı olur.

Öne Çıkan *Özellikler*

- Sensör ve encoder kontrollü sistem ile otomatik ürün boyu algılama ve ayarlama
- Servo kontrollü kesme çenesi ve sürekli çalışma sistemi ile yüksek üretim performansı
- PE ve Poliolefin filmlerle uyumlu, 7–100 mikron aralığında çalışma imkânı
- Farklı ambalaj ölçülerine hızlı adaptasyon ve sürekli ambalaj kalitesi
- 100 ürün hafızası, çok dilli 10" dokunmatik ekran ve USB güncelleme desteği
- Düşük enerji tüketimi ve minimum film sarfiyatı ile verimli üretim
- Hızlı film değişimi ve gergi kontrollü fire sarma sistemi
- Operatör müdahalesi gerektirmeyen tam otomatik üretim yapısı
- Seramik kaplamalı yapıştırma bıçakları ile hassas ve güvenilir yapıştırma
- Ürün, operatör ve makine güvenliği için gelişmiş koruma sistemleri
- CE standartlarına uygun tasarım ve üretim

YOUTUBE LİNK

Opsiyonlar

- Baskılı film kontrol sistemi
- Kapamalı konveyör sistemi
- Tablet veya telefon üzerinden kontrol
- Uzaktan erişim modülü

Max. Kapasite*	65-70 ad/dk	**Max. Konveyör Hızı**	37 m/ min
Mühürleme Barı Uzunluğu	700 mm	**Besleme Voltajı**	380V, 50 Hz
Max. Ürün Ölçüleri	670x200 mm	**Makine Ağırlığı**	950 Kg
Konveyör Bant Genişliği	700 mm	**Film Tipi**	PE - POF (7-100 µ)

**Maksimum kapasite, ürün ebatlarına ve ürün çeşidine göre değişkenlik göstermektedir. En iyi cevap için iletişime geçiniz.*

Birlikte Kullanabileceğiniz *Üniteler*





