Precision Engineering

Maximum Performance



CE

S-5522

CONTINUOUS SIDE SEALER MACHINE







S-5522

CONTINUOUS SIDE SEALER MACHINE

The S Series brings together high speed and premium packaging quality through advanced industrial automation. Constructed with high-grade components and contemporary engineering, it provides durable and reliable operation.
Equipped with a center-folded film feeding architecture, an independent continuous side sealer, and a servo-controlled front sealing jaw, the system guarantees maximum throughput and sealing precision.
The heavy-duty, vibration-free frame ensures smooth, non-stop performance across demanding production lines. Paired with an ergonomic HMI interface, the S Series facilitates streamlined operation with minimal operator requirement.

Highlights
Features

- Automatic product length detection and adjustment via sensor- and encoder-controlled systems.
- High production throughput with a servo-driven sealing jaw and continuous motion operation.
- Wide film compatibility with PE and Polyolefin (POF) films ranging from 7 to 100 microns.
- Rapid adaptation to diverse package dimensions while maintaining consistent wrapping quality.
- 100-recipe memory capacity, 10" multilingual touchscreen HMI, and USB firmware/backup support.
- Cost-effective production through low power consumption and minimized film waste.
- Quick-change film roll mechanism and tension-controlled scrap rewinder.
- Fully automated operational architecture eliminating the need for operator intervention.
- Ceramic-coated sealing blades for precise, clean, and reliable seals.
- Advanced integrated safety systems ensuring product, operator, and machine protection.
- Designed and manufactured in full compliance with CE directives.

YOUTUBE LİNK

Options

- Printed film registration system
- Closing conveyor system
- Control via tablet or smartphone
- Remote access module

Max. Capacity*	65-70 ad/dk	**Max. Conv. Speed**	37 m/ min
Sealing Bar Lenght	520 mm	**Power Supply**	380V, 50 Hz
Max. Product Dimmesion	370 x 200 mm	**Machine Weight**	750 Kg
Conv. Belt Width	550 mm	**Film Type**	PE - POF (7-100 µ)

Units
You can use together







KOTA PACK
Smart Solutions in Packaging

Precision Engineering

Maximum Performance



S-5522

SÜREKLİ KESİM YAN YAPIŞTIRMA SHRİNK MAKİNESİ







S-5522

SÜREKLİ KESİM YAN YAPIŞTIRMA SHRİNK MAKİNESİ

S Serisi makineler, yüksek hız ve üstün ambalaj kalitesini bir araya getiren ileri teknoloji çözümleriyle donatılmıştır. Kaliteli komponentler ve modern mühendislik anlayışıyla tasarlanan sistem, uzun ömürlü ve güvenilir performans sunar.
Çift katlı tek bobin yapısı ile bağımsız yan yapıştırma ve servo kontrollü ön yapıştırma sistemine sahip olan S Serisi, maksimum verimlilik ve hassasiyet sağlar.
Sessiz, titreşimsiz ve sağlam gövde yapısı sayesinde kesintisiz çalışma imkânı sunarken, üretim süreçlerinde yüksek performans ve süreklilik sağlar. Kullanıcı dostu arayüzü ile kolay kullanım sunan S Serisi, minimum operatör müdahalesiyle maksimum üretkenlik elde edilmesine yardımcı olur. ing

Öne Çıkan *Özellikler*

- Sensör ve encoder kontrollü sistem ile otomatik ürün boyu algılama ve ayarlama
- Servo kontrollü kesme çenesi ve sürekli çalışma sistemi ile yüksek üretim performansı
- PE ve Poliolefin filmlerle uyumlu, 7–100 mikron aralığında çalışma imkânı
- Farklı ambalaj ölçülerine hızlı adaptasyon ve sürekli ambalaj kalitesi
- 100 ürün hafızası, çok dilli 10" dokunmatik ekran ve USB güncelleme desteği
- Düşük enerji tüketimi ve minimum film sarfiyatı ile verimli üretim
- Hızlı film değişimi ve gergi kontrollü fire sarma sistemi
- Operatör müdahalesi gerektirmeyen tam otomatik üretim yapısı
- Seramik kaplamalı yapıştırma bıçakları ile hassas ve güvenilir yapıştırma
- Ürün, operatör ve makine güvenliği için gelişmiş koruma sistemleri
- CE standartlarına uygun tasarım ve üretim

YOUTUBE LİNK

Opsiyonlar

- Baskılı film kontrol sistemi
- Kapamalı konveyör sistemi
- Tablet veya telefon üzerinden kontrol
- Uzaktan erişim modülü

Max. Kapasite*	65-70 ad/dk	**Max. Konveyör Hızı**	37 m/ min
Mühürleme Barı Uzunluğu	520 mm	**Besleme Voltajı**	380V, 50 Hz
Max. Ürün Ölçüleri	370 x 200 mm	**Makine Ağırlığı**	750 Kg
Konveyör Bant Genişliği	550 mm	**Film Tipi**	PE - POF (7-100 µ)

**Maksimum kapasite, ürün ebatlarına ve ürün çeşidine göre değişkenlik göstermektedir. En iyi cevap için iletişime geçiniz.*

Birlikte Kullanabileceğiniz *Üniteler*





